#### REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Service, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget,

Paperwork Reduction PLEASE DO NO	n Project (0704-0188) \ OT RETURN YO	Washington, DC 20503 <b>UR FORM TO TH</b>	3. HE ABOVE ADDRES	SS.			
1. REPORT DATE (DD-MM-YYYY) 2. R			PORT TYPE			3. DATES COVERED (From - To)	
	ULY 2010		Conf Pa	aper (Briefing Cl		April 2008 – January 2009	
4. TITLE AND SUBTITLE					<b>5a. CONTRACT NUMBER</b> FA8750-08-C-0157		
SEMANTIC SEARCH WITH SELF-MAINTAINING CLASSES  5							
					5b. GRANT NUMBER		
						N/A	
					5c. PROGRAM ELEMENT NUMBER		
					65502F		
6. AUTHOR(S)					5d. PROJECT NUMBER		
					08SB		
Terry Patten and Stephen Hookway					5e. TASK NUMBER		
						IR	
					5f. WORK UNIT NUMBER		
31.					31. WOI	75	
7 DEDECORMIN	IC ODC ANIZATI	ON NAME(C) AN	ID ADDRESS(ES)			8. PERFORMING ORGANIZATION	
7. PERFORMIN	IG ORGANIZATI	ON NAME(5) AN	ND ADDRESS(ES)			8. PERFORMING ORGANIZATION REPORT NUMBER	
Charles River Analytics, Inc.							
625 Mount Auburn Street, Suite 3						N/A	
Cambridge, MA 02138-4555							
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)					10. SPONSOR/MONITOR'S ACRONYM(S)		
N/A							
AFRL/RIEB 525 Brooks Road						11. SPONSORING/MONITORING	
Rome NY 13441-4505						AGENCY REPORT NUMBER	
						AFRL-RI-RS-TP-2010-33	
12. DISTRIBUTION AVAILABILITY STATEMENT							
APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED. PA #: 88ABW-2010-3417 Date Cleared: 21-June-2010							
13. SUPPLEMENTARY NOTES							
This work was funded in whole or in part by Department of the Air Force contract number FA8750-08-C-0157. The U.S.							
Government has for itself and others acting on its behalf an unlimited, paid-up, nonexclusive, irrevocable worldwide license to use,							
modify, reproduce, release, perform, display, or disclose the work by or on behalf of the Government.							
14. ABSTRACT The SDID contract entitled Knowledge heard Access and Date Internation (KADI) resulted in a narrow being respected at the 2010							
The SBIR contract entitled Knowledge-based Access and Data Integration (KADI) resulted in a paper being presented at the 2010 International Conference on Semantic Web and Web Services held at Las Vegas, NV on 12-15 July-2010.							
international Conference on Demande 1100 and 1100 Del 1000 held at Las 108as, 111 on 12 13 sury 2010.							
15. SUBJECT TERMS Semantic Integration, Imagery, Intelligence Surveillance Reconnaissance, Service Oriented Architecture							
Semantic Integration	gration, Imagei	ry, Intelligence	Surveillance Reco	onnaissance, Serv	rice Orien	ted Architecture	
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF	18. NUMBER	19a. NAME OF RESPONSIBLE PERSON		
			ABSTRACT	OF PAGES		N. Haritatos	
a. REPORT	b. ABSTRACT	c. THIS PAGE	1111	12		HONE NUMBER (Include area code)	
U	U	U	UU	12	N/A		

### Semantic Search With Self-Maintaining Classes

Prepared for:

SWWS 2010 Las Vegas

This work was supported by US Air Force Contract FA8750-08-C-0157

12-15 July 2010

Presented by:

Terry Patten

Stephen Hookway

www.cra.com

#### Background

- Semantic search is all about inferring membership in query classes
- Traditionally, semantic search has focused on class-subclass inference (subsumption)
  - Query: Aircraft
  - Match: MiG-23
    - Subclass of Fighter
      - Subclass of MilitaryAircraft
        - Subclass of Aircraft
- Most often, classes are enumerated through subsumption trees
- But class membership can also be inferred using
  - Logic (a class is the intersection of several other classes)
  - Properties (a class includes any x that has property y)
- In general, class membership descriptions can be complex
  - In OWL 2 these are called "Class Expressions"
  - In Description Logic these are called "Complex Concepts"

## Class Expressions and Semantic Search

- Inferring class membership using class expressions is a powerful semantic search technique because:
  - It provides a mechanism loosely analogous to database "views"
    - Alternate ways of organizing information can be built on top of an existing ontology
  - Query classes do not have to reflect the subsumption hierarchy
  - Query classes do not have to be enumerated
- The inferred classes are self-maintaining because their membership automatically changes as the membership of underlying classes changes

## A Case Study: Threats to Air Operations

- Problem: Air Force analysts searching image metadata for "threats to air operations"
- Currently, these searches are done using keywords
- But there may be many names for weapon systems:
  - NATO designations
  - Coalition partner names
  - Anglicized manufacturer names
- Having to include all these names in queries places a burden on the analyst
  - An ontology can keep track of all these names
  - This is an old technique: using a thesaurus to expand a query
- But even with only one term for each weapon, there are still a lot of weapons to list
- We would like to search for whole classes of threats

#### Searching for Threat Classes

- Threats to air operations include members of traditional weapons classes such as:
  - Aircraft
  - Missiles
  - Artillery
- But not all members of these traditional military classes are threats to air operations
  - Bombers are aircraft, but are not really a threat to an air operation
  - Ballistic missiles are not a threat
  - Surface-to-surface artillery is not a threat
- It is tempting to enumerate the threats to air operations
  - What are all the types of Threats from the air ...
  - What are all the types of Threats from the surface ...
- A better idea is to infer threats based on weapon properties

#### Inferring Threats from Properties

- Using OWL-DL we can say that the class of weapons that fires air-to-air missiles is a subclass of threats to air operations
- We don't have to say (explicitly) what weapons are in that class—they are inferred based on the property
- We don't have to know (or care) where in the ontology such weapons exist
- This technique allows us to cut across existing subsumption hierarchies and create alternate views of the knowledge

 In particular, we can create views that line up well with useful queries

#### Example: BM-21

- The BM-21 is a multiple-rocket launcher
  - Classic surface-to-surface artillery
- But adversaries modified the rockets
  - Used timed-fuzes
- And pointed the weapon straight up
  - Rockets become heavy flak



- The list of munitions that the BM-21 fires is updated to include these modified, now anti-aircraft rockets
- Since weapons that fire anti-aircraft artillery munitions are a subclass of threats to air operations...
  - The BM-21 automatically becomes a threat as soon as that property appears

#### OWL-DL Class Expression that Matches BM-21

- This class expression defines—and maintains—a useful class
  - Prior to having anti-aircraft munitions, the BM-21 it is not a member of this class
  - Once the BM-21 fires anti-aircraft munitions it automatically becomes a member of this class

#### Case Study Summary

- Weapons are threats to air operations if they
  - Fire air-to-air missiles
  - Fire surface-to-air missiles
  - Fire anti-aircraft artillery munitions
  - Etc.
- We define a class expression for each of these
- And make them all subclasses of "ThreatsToAirOperations"
- Weapons automatically become members of the Threat class if they match the class expressions
- The class expressions automatically maintain class membership
- For scalable OWL-DL, we are implementing our semantic search using PelletDb (<a href="http://clarkparsia.com/pelletdb/">http://clarkparsia.com/pelletdb/</a>)
  - A tight integration of Pellet and Oracle Semantic Technology

#### Generality of Search Using Self-Maintaining Classes

- This technique can be used in any domain where some query classes do not line up well with the subsumption hierarchy
- Some non-military possibilities:
  - Find me all the risky investments ...
  - Find me all the high-performance cars ...
  - Find me all the dangerous substances ...

• ...

#### Questions?

# QUESTIONS?

charles river analytics

- + Charles River Analytics Inc.
- 625 Mount Auburn St.
- Cambridge, MA 02138
- p: 617.491.3474
- f: 617.868.0780